

IT'S NOT A
TRACTOR, IT'S A
STEINER



450

GO WHERE OTHERS WON'T.
DO WHAT OTHERS CAN'T.

▶ **LEGENDARY CLIMBING AND MANEUVERABILITY**

The 450's articulating frame provides a tight turning radius of 43.5 inches for agile maneuverability in tight areas. The frame oscillates to keep you balanced and in control when side-mowing slopes. With a low center of gravity and 4-wheel drive, you get unmatched traction and stability for scaling slopes and berms.

▶ **EXCLUSIVE HYDRAULIC WEIGHT TRANSFER AND TRACTION BOOST SYSTEM**

The new, integrated hydraulic weight transfer and traction boost system provides additional traction and control when needed. It provides consistent weight transfer through the full range of lift arm travel with no secondary springs to adjust, and it is fully adjustable on demand. Now with dual hydraulic filtration.

▶ **A CHOICE OF POWERFUL ENGINES**

Choose from three reliable engines: a Kubota® 25-horsepower liquid-cooled diesel, a Kubota® 32-horsepower liquid-cooled gasoline, or a 37-horsepower Vanguard EFI™ gasoline engine.

▶ **USE ANYWHERE, ANYTIME**

Bright, efficient LED headlights and taillights provide plenty of light when needed. A 7-gallon, durable, roto-molded fuel tank keeps you going longer without stopping to refuel.

▶ **TOUGH AND POWERFUL TRANSAXLES**

Durable Peerless® 2600 dual range transaxles are tough and powerful enough to handle the most rigorous tasks and terrain. You get plenty of torque for productive ground speeds up to 9.5 mph in high gear and 6 mph in low gear.

▶ **COMFORTABLE RIDE, EASY CONTROL**

The 450 features a large operator platform and conveniently located controls for easy operation. Improved hydraulic performance provides smooth, predictable steering and reduced foot pedal force for easy, hands-free speed control. Ride in comfort with the new adjustable, high-back suspension seat with armrests.

▶ **QUICK-HITCH SYSTEM**

Steiner's convenient and easy-to-use two-point Quick-Hitch™ System, with 50% stronger lift arms, make switching attachments virtually effortless. In a few minutes and without tools required, you're on to the next task.

▶ **ATTACHMENT DRIVES**

An auxiliary hydraulic system with hydraulic quick-couplers help you finish chores with our optional hydraulic attachments. A front-mounted Warner® MagStop PTO clutch drives belt-driven attachments with power to spare.

▶ **IMPROVED HYDRAULICS**

A new stacked gear pump design dramatically increases durability and hydraulic performance and efficiency, with increased oil cooler capacity and reduced drive system pressure. Provides 1,750 PSI of steering and lift pressure for more hydraulic power to handle the toughest chores.

▶ **MORE STANDARD FEATURES**

A folding rollover protective structure, heavy-duty front and rear skid plates, an integral-frame rear weight bar, a heavy duty rear-mounted 2-inch receiver hitch and a 12-volt electrical outlet are all standard on the 450.



GO

**WHERE
OTHERS
WON'T.**

DO

**WHAT
OTHERS
CAN'T.**



450 TRACTOR SPECIFICATIONS



Dimensions:

Overall Width: 44.5," 66.5" with dual wheels
 Overall Length: 80.5" with ROPS up
 Overall Height: 73.5" with ROPS up
 55" with ROPS folded
 Wheelbase (front to rear axle): 43.5"
 Minimum Ground Clearance: 4.75"
 Frame Oscillation: 9"
 Frame Articulation: 36 degrees, 43.5" turning radius

Hydraulics:

Implement Pump: Turolla Group 2 Series
 Fixed Displacement, Stacked Configuration
 Flow Capacity (gpm): 6 gpm @ 3600 RPM
 Lift, Steering, Auxiliary Pressure: 1750 PSI
 Hydraulic Oil Capacity: 5.25 US Gallons

Transmission:

Drive Train: Eaton® model 70160, Variable Displacement Piston Pump
 Transaxles: (2) Peerless® 2600 Dual Range
 Speeds: 0-9.5 MPH, High; 0-6 MPH, Low
 Steering: Hydraulic Power Steering
 Brakes: Dual Disc and Front and Rear Axles

Attachment Drive:

Front PTO Clutch: Warner® CMS 250 Series Electric Clutch/Brake
 Hydraulic Outlets: Quick Couplers-Front

Fuel System:

7 US Gallon Tank Capacity

Wheels:

Field Trac (All Terrain) 22x12-10
 Mag Off Road (Bar) 22x12-10
 Lightfoot (Turf) 22x11-10

Hitch:

Front: Steiner Quick-Hitch™, with standard front release control
 Back: Standard 2" receiver hitch, with optional category 1 three-point hitch

High-Back Bucket Seat with Rear Storage Pouch:

Armrests: Standard
 Suspension: Radial Bearing Suspension, optional Mechanical Suspension
 Adjustment: 6" Fore and Aft

Additional Features:

Lighting: Dual LED Headlights and Taillights
 Storage Compartment: Standard
 Cup Holder: Standard
 PTO Tension Adjustment: Manual
 12 Volt Outlet: Standard – 15 Amp

► MODEL SPECIFICATIONS

| Model # | 75-75025 | 75-75032 | 75-75037 |
|---|--------------|---------------|-------------------|
| Engine | Kubota® D902 | Kubota® WG972 | Vanguard™ M61 EFI |
| Max Operating Speed | 3600 rpm | 3600 rpm | 3600 rpm |
| Fuel Type | Diesel | Gasoline | Gasoline |
| Horsepower (Gross) | 25 hp | 32.5 hp | 37 hp |
| Displacement | 898 cc | 962 cc | 993 cc |
| Cylinders | 3 | 3 | 2 |
| Cooling | Liquid | Liquid | Air |
| Fuel Capacity | 7 gal | 7 gal | 7 gal |
| Charging | 40 Amp | 40 Amp | 50 Amp |
| Battery | 630 CCA | 450 CCA | 450 CCA |
| Slope Rating, Continuous | 20° Max | 20° Max | 20° Max |
| Slope Rating, Intermittent (10 minutes or less) | 30° Max | 30° Max | 30° Max |
| Weight (with Field Trac tires and fuel) | 1665 lb | 1660 lb | 1575 lb |

Steiner uses commercial-strength engine options for longevity and ease of service. All engines are warranted by their respective manufacturer and your local dealer. The power engine ratings are provided by the engine manufacturer. Actual power output is dependent on many factors including engine rpm, air density and engine condition.



All Steiner products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner products, visit your Steiner dealer today.
 For the location of the dealer nearest you, call 1-866-469-1242 or 1-920-699-2000.
 Visit us on the Web at www.steinerturf.com



Steiner® is a registered trademark of Schiller Grounds Care, Inc.
 ©2017 Schiller Grounds Care, Inc. Company. All rights reserved. Steiner | One BOB-CAT Lane | Johnson Creek, WI 53038